

DMX Correlative DMX512

6,50mm; black

Art. No.: NL-D110



General Data

Article number :	NL-D110
Name :	Correlative DMX512
Properties :	Analog
Properties :	OFC oxygen free copper
Properties :	Digital 110 Ω AES / EBU
Application area :	Stage / live
Application area :	outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 110 V
Application :	DMX
Colour :	black

Technical Data

Signal transmission :	symmetrical
Construction :	[2(2LI2YS0,34mm ²)(ST)]CY
Jacket material :	PVC
Jacket Ø [mm] :	6,50
Number of Channels (AES/EBU, DMX) :	1
Inner conductor (AES/EBU, DMX) :	2
Inner conductor (AES/EBU, DMX) [mm ²] :	0,34
Inner conductor Ø (AES/EBU, DMX) [mm] :	0,66
AWG (AES/EBU, DMX) :	22
Shielding :	Copper-cross mesh, tined + AL / PT foil
Shielding factor [%] :	100
Copper strands (AES/EBU, DMX) :	19
Copper strand Ø (AES/EBU, DMX) [mm] :	0,15
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,50
Weight per 1 m [g] :	50
UV-resistant :	yes
Fire load per m [kWh] :	0,17

Style variant :	round
Packing :	100 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	80
Width [mm] :	6,5
Height [mm] :	6,5

Electrical Data

Capac. cond./cond. per 1 m (AES/EBU, DMX) [pF] :	58
Capac. cond./shield. per 1 m (AES/EBU, DMX) [pF] :	100
Impedance [Ω] :	110
Insulation resist. per 1 km [GΩ] :	5
Insulation resist. per 1 km (AES/EBU, DMX) [GΩ] :	5
Conductor resistance per 1 km [Ω] :	53
Shield. resistance per 1 km [Ω] :	15

UK Sales Office address:

128 City Road, London, United Kingdom, EC1V 2NX.
+44 20 3908 80 10
sales@nordlyslight.com

Factory address:

Lydehøjvej 6, 4720 Præstø, Denmark
+45 28 60 25 80
info@nordlyslight.com