

# Microphone Cable

## PVC Ø 6,50mm; Black

Art. No.: NL-M600

; 2 x 0.34mm<sup>2</sup>



### General Data

Article number :	NL-M600
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	Microphone Cable
Colour :	black

### Technical Data

Signal transmission :	symmetrical
Construction :	[2(2LI2YS0,34mm <sup>2</sup> )(ST)]CY
Jacket material :	PVC
Jacket Ø [mm] :	6,5
Number of Channels (AES/EBU, DMX) :	1
Inner conductor (AES/EBU, DMX) :	2
Inner conductor (AES/EBU, DMX) [mm <sup>2</sup> ] :	0,34
Inner conductor Ø (AES/EBU, DMX) [mm] :	0,66
AWG (AES/EBU, DMX) :	22
Shielding :	Copper braided shielding with 0.10 mm indiv. Strands
Shielding factor [%] :	100
Copper strands :	19
Copper strand Ø [mm] :	0,15
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,50
Weight per 1 m [g] :	50
UV-resistant :	yes
Fire load per m [kWh] :	0,22

Style variant :	round
Packing :	100 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	80
Width [mm] :	6,5
Height [mm] :	6,5

### Electrical Data

Capac. cond./cond. per 1 m [pF] :	115
Capac. cond./shield. per 1 m [pF] :	100
Impedance [Ω] :	600
Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1 km [GΩ] :	1
Conductor resistance per 1 km [Ω] :	55
Shield. resistance per 1 km [Ω] :	25

### UK Sales Office address:

128 City Road, London, United Kingdom, EC1V 2NX.  
+44 20 3908 80 10  
sales@nordlyslight.com

### Factory address:

Lydehøjvej 6, 4720 Præstø, Denmark  
+45 28 60 25 80  
info@nordlyslight.com